



Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03003](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

170-03003



Article Number: 170-03003

Expandable Braided Sleeve, 1.0" Dia., Black, 65.0 ft/Standard Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03003

Type BSP100

Color Black (BK)

- Features and Benefits**
- Weave construction adjusts to twisting and flexing without creating wrinkles or bends.
 - Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus.
 - Color options available to provide easy visual and safety identification of critical wiring components.
 - Expands to 150% of nominal diameter for fast, easy installation.

Product Description General purpose expandable braided sleeve provides flexible abrasion protection for wire bundles and hoses.

Short Description Expandable Braided Sleeve, 1.0" Dia., Black, 65.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 65.0 ft

Length L (Metric) 19.8 m

Reel Length (imperial) 65.0 ft

Bundle Diameter Min. (Imperial) 0.625 "

Bundle Diameter Min. (Metric) 15.9 mm

Bundle Diameter Max. (Imperial) 1.625 "

Bundle Diameter Max. (Metric) 41.3 mm

Nominal Diameter (Imperial) 1 "

Nominal Diameter (Metric) 25.4 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 65 ft

Package Quantity (Metric) 65.0 ft

Weight (Metric) 0.40 kg

Weight (imperial) 0.87 lbs

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability FAR 25
FMVSS



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03003 - 1" PET BRAIDED SLEEVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Halogenfree Yes

Operating Temperature -94°F to +257°F (-70°C to +125°C)

ROHS Compliant Yes

UL Recognized (US and Canada) Yes