



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03107 - 3/4" PLENUM RATED SLEEVING

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[170-03107](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

170-03107



Article Number: 170-03107

Plenum Rated Expandable Braided Sleeveing (Halar), 0.75" Dia., White, 75.0 ft/Reel



Download drawing



Download spec sheet

## Base Data

Local Order Number 170-03107

Type BSHLR3410

Color White (WH)

**Features and Benefits**

- Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.
- Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.
- Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

**Product Description** Halar self-extinguishing sleeveing is used where flammability, high temperature endurance and low outgassing are the primary concern.

**Short Description** Plenum Rated Expandable Braided Sleeveing (Halar), 0.75" Dia., White, 75.0 ft/Reel

## Product Dimensions

Length L (Imperial) 75.0 ft

Length L (Metric) 22.9 m

Reel Length (imperial) 75.0 ft

Bundle Diameter Min. (Imperial) 0.5 "

Bundle Diameter Min. (Metric) 12.7 mm

Bundle Diameter Max. (Imperial) 1.25 "

Bundle Diameter Max. (Metric) 31.8 mm

Nominal Diameter (Imperial) 3/4 "

Nominal Diameter (Metric) 19.1 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 75 ft

Weight (imperial) 1.28 lbs

Weight (Metric) 0.58 kg

## Material and Specifications

Material Polyamide 6.6 (E/CTFE)

Material Shortcut E/TFE

Flammability UL VW-1  
FAR 25

Operating Temperature -103°F to +302°F (-75°C to +150°C)



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-03107 - 3/4" PLENUM RATED SLEEVING

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**ROHS Compliant** Yes

**Certification/Specification** UL2024

**UL Recognized (US and Canada)** Yes