



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03114 - 2" PLENUM BRAIDED SLEEVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[170-03114](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

170-03114



Article Number: 170-03114

Plenum Rated Expandable Braided Sleeving (Halar), 2.0" Dia., Black, 50.0 ft/Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03114

Type BSHLR200

Color Black (BK)

Features and Benefits

- Meets UL 2024 and NFPA 262 specifications meets requirements for use in plenum applications.
- Technically advanced monofilament material is rated as low smoke, flame resistant and can withstand exposure to Cobal 60 radiation.
- Exceeds requirements of FMVSS 302 as well as aviation industry requirements of FAR25.

Product Description Halar self-extinguishing sleeving is used where flammability, high temperature endurance and low outgassing are the primary concern.

Short Description Plenum Rated Expandable Braided Sleeving (Halar), 2.0" Dia., Black, 50.0 ft/Reel

Product Dimensions

Length L (Imperial) 50.0 ft

Length L (Metric) 15.2 m

Reel Length (imperial) 50.0 ft

Bundle Diameter Min. (Imperial) 1.5 "

Bundle Diameter Min. (Metric) 38.1 mm

Bundle Diameter Max. (Imperial) 3.5 "

Bundle Diameter Max. (Metric) 88.9 mm

Nominal Diameter (Imperial) 2 "

Nominal Diameter (Metric) 50.8 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 50 ft

Package Quantity (Metric) 50.0 ft

Weight (imperial) 2.3 lbs

Weight (Metric) 1.04 kg

Material and Specifications

Material Polyamide 6.6 (E/CTFE)

Material Shortcut E/TFE

Flammability UL VW-1
FAR 25



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 170-03114 - 2" PLENUM BRAIDED SLEEVING

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Operating Temperature -103°F to +302°F (-75°C to +150°C)

ROHS Compliant Yes

Certification/Specification UL2024

UL Recognized (US and Canada) Yes