



## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:


[HellermannTyton](#)  
[170-21200](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## 170-21200



**Article Number:** 170-21200

**Helagaine Braided Sleeveing, 12.0 mm Dia, Polyamide 6.6, Gray, 328ft/Reel**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** 170-21200

**Type** HEGPA6612

**Color** Gray (GY)

**Features and Benefits**

- Nylon monofilament construction weave offers a tight braid that provides full coverage but will not rot or retain moisture.
- Material performs well in wet applications and where abiding substrate has a smooth surface.

**Product Description** Helagaine Nylon Polyamide Expandable Braided Sleeveing is a pliable yet durable sleeve that protects against cuts, abrasion and excessive wear caused by repetitive motion.

**Short Description** Helagaine Braided Sleeveing, 12.0 mm Dia, Polyamide 6.6, Gray, 328ft/Reel

### Product Dimensions

**Length L (Imperial)** 328.0 ft

**Length L (Metric)** 100.0 m

**Reel Length (imperial)** 328.0 ft

**Bundle Diameter Min. (Imperial)** 0.32 "

**Bundle Diameter Min. (Metric)** 8 mm

**Bundle Diameter Max. (Imperial)** 0.55 "

**Bundle Diameter Max. (Metric)** 14 mm

**Nominal Diameter (Imperial)** 1/2 "

**Nominal Diameter (Metric)** 12 mm

**Braid Density** n. 85%

### Logistics and Packaging

**Quantity Per** metre

**Package Quantity (Metric)** 100 m

**Carton Quantity** 100 Meter

**Weight (Metric)** 1.1 kg

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2  
FMVSS 302

**Halogenfree** Yes



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 170-21200 - 5/16" HELAGINE POLY BRDD SLVG

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Operating Temperature** -76°F to +302°F (-60°C to +150°C)

**ROHS Compliant** Yes

**Certification/Specification** EN 45545: 2013