

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[181-00189](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

181-00189

**Article Number:** 181-00189

**Solid Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, White, 30ft/Box**



Download spec sheet

## Base Data

**Local Order Number** 181-00189

**Type** SD1X3

**Color** White (WH)

**Features and Benefits**

- A temporary film is applied to the covers to protect against scratches and is writable for identification during installation.
- Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.
- Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily snap on and off. (Covers to be purchased separately)

**Product Description** HellermannTyton's Pro-Duct solid wall wiring duct efficiently routes and protects wires and cables. Solid wall wiring duct is designed for straight wire runs where breakouts are not required. Pro-Duct solid wall wiring duct is manufactured from high-impact, rigid PVC, and is available in 6-foot lengths in standard colors of white, gray and black.

**Short Description** Solid Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, White, 30ft/Box

## Product Dimensions

**Length L (Imperial)** 6.0 ft

**Length L (Metric)** 1.83 m

**Width W (Imperial)** 1.0 "

**Width W (Metric)** 25.4 mm

**Width W2 (Imperial)** 1.0 "

**Width W2 (Metric)** 25.4 mm

**Height H (Imperial)** 3.07 "

**Height H (Metric)** 77.9 mm

**Mounting Hole Centers (Imperial)** 4.0 "

## Logistics and Packaging

**Quantity Per** box

**Package Quantity** 30.0 ft

**Package Quantity (Metric)** 9.1 m

**Carton Quantity** 120.0 ft

## Material and Specifications

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** self-extinguishing



**Operating Temperature** +122°F (+50°C)

**ROHS Compliant** Yes

**Certification/Specification** UL  
CSA

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** No

**UL Recognized (US)** Yes