Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton 181-15503

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 181-15503 - SOLID WALL DUCT 1.5X1.5

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

HellermannTyton

181-15503

Article Number: 181-15503

Solid Wall Wiring Duct, 1.5" X 1.5", Non-Adhesive, PVC, White, 120ft/Carton







Base Data

Local Order Number 181-15503

Type SD1.5X1.5 Color White (WH)

Features and Benefits • A temporary film is applied to the covers to protect against scratches and is writable for identification during

installation.

· Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

· Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily

snap on and off. (Covers to be purchased separately)

Product Description HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring

> duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6

foot lengths.

Solid Wall Wiring Duct, 1.5" X1.5", Non-Adhesive, PVC, White, 120ft/Carton Short Description

Product Dimensions

Length L (Imperial)

Length L (Metric) 1.83 m

Width W (Imperial) 1.5 "

Width W (Metric) 38.1 mm

Width W2 (Imperial) 1.5 "

Width W2 (Metric) 38.1 mm

Height H (Imperial) 1.57 "

Height H (Metric) 39.9 mm

Mounting Hole Centers (Imperial) 4.0 "

Logistics and Packaging

Quantity Per

Package Quantity 120.0 ft

Package Quantity (Metric) 36.6 m

Carton Quantity 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 181-15503 - SOLID WALL DUCT 1.5X1.5

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA

UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) No

UL Recognized (US) Yes

© HellermannTyton 2015