# **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton 181-21002

For any questions, you can email us directly: <a href="mailto:sales@integrated-circuit.com">sales@integrated-circuit.com</a>



# Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 181-21002 - SOLID WALL DUCT 2X1

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

# HellermannTyton

### 181-21002

Article Number: 181-21002

Solid Wall Wiring Duct, 2" X 1", Non-Adhesive, PVC, White, 30ft/Box







#### **Base Data**

Local Order Number 181-21002

Type SD2X1

Color White (WH)

Features and Benefits • A temporary film is applied to the covers to protect against scratches and is writable for identification during

installation.

· Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

· Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily

snap on and off. (Covers to be purchased separately)

Product Description

HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6

foot lengths.

Short Description Solid Wall Wiring Duct, 2" X1", Non-Adhesive, PVC, White, 30ft/Box

## **Product Dimensions**

Length L (Imperial)

Length L (Metric) 1.83 m

Width W (Imperial) 2.0 "

Width W (Metric) 50.8 mm

Width W2 (Imperial) 2.0 "

Width W2 (Metric) 50.8 mm

Width W6 (imperial) 0.5 "

Width W6 (metric) 12.7 mm

Height H (Imperial) 1.06 "

Height H (Metric) 26.9 mm

Mounting Hole Centers (Imperial) 4.0 "

## **Logistics and Packaging**

Quantity Per box

Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 120.0 ft

## Material and Specifications



# Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 181-21002 - SOLID WALL DUCT 2X1

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Material Shortcut PVC

Flammability self-extinguishing

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA

IJ

UL Listed (US and Canada) No

UL Recognized (US and Canada) No

UL Recognized (US) Yes

© HellermannTyton 2015