

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton 181-33006

For any questions, you can email us directly: <u>sales@integrated-circuit.com</u>



## HellermannTyton

## 181-33006

181-33006		
Ar	ticle Number: 181-33006	
	olid Wall Wiring Duct, 3" X 3", Non-Adhesive, PVC, White, 120ft/Carton	
Y		
Y	RoHS	
Download drawing Download	d spec sheet	
Base Data		
Local Order Number	181-33006	
Туре	SD3X3	
Color	White (WH)	
Features and Benefits		
	<ul><li>installation.</li><li>Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.</li></ul>	
	• Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily	
	snap on and off. (Covers to be purchased separately)	
Product Description	HellermannTyton's Pro-Duct, Solid Wall wiring duct efficiently routes and protects wire and cable. Solid Wall wiring duct it designed for straight wire runs where break outs are not required. Pro-Duct, Solid Wall wiring duct is	
	manufactured from high impact, rigid PVC, comes in standard colors of white, gray and black, and is available in 6	
Short Description	foot lengths.	
Short Description	Solid Wall Wiring Duct, 3" X 3", Non-Adhesive, PVC, White, 120ft/Carton	
Product Dimensions		
Length L (Imperial)	6.0 ft	
Length L (Metric)	1.83 m	
Width W (Imperial)	3.0 "	
Width W (Metric)	76.2 mm	
Width W2 (Imperial)	3.0 "	
Width W2 (Metric)	76.2 mm	
Width W6 (imperial)	1.0 "	
Width W6 (metric)	25.4 mm	
Height H (Imperial)	3.07 "	
Height H (Metric)	77.9 mm	
Mounting Hole Centers (Imperial)	4.0 "	
Logistics and Packaging		
Quantity Per	carton	
Package Quantity		
Package Quantity (Metric)		
Carton Quantity		
Surton Quantity		

## Material and Specifications

Matorial	Polyvinylchloride (F	
Material	POW/INVICTIONCE (F	



Material Shortcut	PVC
Flammability	self-extinguishing
Operating Temperature	+122°F (+50°C)
<b>ROHS</b> Compliant	Yes
Certification/Specification	UL CSA
UL Listed (US and Canada)	No
UL Recognized (US and Canada)	No
UL Recognized (US)	Yes

© HellermannTyton 2015