

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[184-15300](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

184-15300

Article Number: 184-15300

High Density Slotted Wall Wiring Duct, 1.5" X 3", Non-Adhesive, PVC, Gray, 30ft/Box



Download spec sheet

Base Data

Local Order Number 184-15300

Type SLHD1.5X3

Color Gray (GY)

Features and Benefits

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

Product Description Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

Short Description High Density Slotted Wall Wiring Duct, 1.5" X 3", Non-Adhesive, PVC, Gray, 30ft/Box

Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 1.5 "

Width W (Metric) 38.1 mm

Width W2 (Imperial) 1.5 "

Width W2 (Metric) 38.1 mm

Width W3 (Imperial) 0.16 "

Width W3 (Metric) 4.1 mm

Width W4 (imperial) 0.4 "

Width W4 (metric) 10.2 mm

Width W5 (imperial) 2.6 "

Width W5 (metric) 66.0 mm

Height H (Imperial) 3.07 "

Height H (Metric) 77.9 mm

Mounting Hole Centers (Imperial) 2.0 "

Logistics and Packaging

Quantity Per box

Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 120.0 ft

Material and Specifications

| | |
|--------------------------------------|-------------------------|
| Material | Polyvinylchloride (PVC) |
| Material Shortcut | PVC |
| Flammability | self-extinguishing |
| Operating Temperature | +122°F (+50°C) |
| ROHS Compliant | Yes |
| Certification/Specification | UL CSA |
| UL Listed (US and Canada) | No |
| UL Recognized (US and Canada) | No |
| UL Recognized (US) | Yes |