



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 211-60040 - PCLAMP .3937" MAXBUNDIA .255"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[211-60040](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

211-60040



Article Number: 211-60040

P Clamp, .39" Width, .26" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 1000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 211-60040

Type H3P

Color Black (BK)

Features and Benefits

- P-Clamps easily guide and locate wire and cables up to 1" in diameter.
- Designed with a radiused edge to prevent chaffing and cutting into insulation.

Product Description HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.

Short Description P Clamp, .39" Width, .26" Max Bundle Dia, .17" Mounting Hole Dia, PA66HS, Black, 1000/pkg

Product Dimensions

Fixation Method screw-hole

Variant Closed

Width W (Imperial) 0.39 "

Width W (Metric) 10.0 mm

Bundle Diameter Max. (Imperial) 0.26 "

Bundle Diameter Max. (Metric) 6.5 mm

Mounting Hole Diameter D (Imperial) 0.17 "

Mounting Hole Diameter D (Metric) 4.2 mm

Nominal Diameter (Imperial) 1/4 "

Nominal Diameter (Metric) 6.5 mm

Wall Thickness WT (Imperial) .03937 "

Wall Thickness WT (Metric) 1.0 mm

Mounting Hole Centers (Imperial) 0.39 "

Mounting Hole Diameter D Max. 4.2 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 4.2 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000 Pieces

Carton Quantity 8000 Pieces

Weight (Metric) 0.4 kg

Material and Specifications



Material Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Flammability UL94 V2

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes