



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 553-50037 - YELLOW SHRINK TRAK .75" 500/BX

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[553-50037](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

553-50037



Article Number: 553-50037

Heat Shrink Label, .75" 1-Slit Single Sided, Polyolefin, Yellow, 500/BX



Download spec sheet

Base Data

Local Order Number 553-50037

Type HST18-6YE-S

Color Yellow (YE)

- Features and Benefits**
- Slide Slit and optional center slits for easy wire insertion.
 - Smooth surface for clean and legible printing.
 - Supplied on a ladder style carrier so that markers can be kitted after printing.
 - A 3:1 shrink ratio means fewer skews as each marker covers a wider range of wire diameters.

Product Description HellermannTyton's ShrinkTrak heat shrinkable markers make it easy to mark wire, cable and other components. The military approved heat shrink tubing is flattened and assembled in a ladder style carrier system for easy printing using a thermal transfer printer. The ladder system creates a kit of markers that can be sorted, removed and applied in any order thus saving time, labor and speeding production.

Short Description Heat Shrink Label, .75" 1-Slit Single Sided, Polyolefin, Yellow, 500/BX

Product Dimensions

Length L (Imperial) 0.95 "

Length L (Metric) 24 mm

Printable (Yes/No) Yes

Variant Thin-Wall

Width W (Imperial) 0.95 "

Width W (Metric) 24 mm

Height H (Imperial) 1.20 "

Height H (Metric) 30.48 mm

Diameter Max. (Imperial) 0.75 "

Outside Diameter Max. (Imperial) 0.75 "

Outside Diameter Max. (Metric) 19.05 mm

Wall Thickness WT (Imperial) 0.036 "

Wall Thickness WT (Metric) 1.00 mm

Print Method Thermal Transfer

Recovered Diameter d (metric) 6.0 mm

Recovered Diameter d (imperial) 0.25 "

Supplied Diameter D (metric) 18.0 mm

Supplied Diameter D (imperial) 0.732 "

Thickness T (Metric) 3.0 µm

Width of Liner WL (imperial) 3.0 "

Width of Liner WL (metric) 76.2 mm

Width of Printable Area (imperial) 0.95 "

Width of printable area (metric) 24.10 mm

Logistics and Packaging

Quantity Per box

Package Quantity 500

Package Quantity (Metric) 500

Markers per row 2

Weight (Metric) 0.68 kg

Weight (imperial) 1.48 lbs

Material and Specifications

Material Polyolefin, cross-linked (PO-X)

Material Shortcut PO-X

US MILSPEC AMS-DTL-23053/5 Class 1 and 3
MIL-STD-202G Method 215K
SAE-AS81531

Dielectric Strength (Metric) 19.7 kV min.

Flammability UL224 VW-1

Shrink Temperature +194 °F (+90 °C)

Operating Temperature -67°F to +275°F (-55°C to +135°C)

ROHS Compliant Yes

Certification/Specification SAE - AMS - DTL-23053/5 Class 1 and 3
SAE-AS81531
MIL-STD-202G Method 215K
UL224 125 °C 600V VW-1