



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 596-00183 - POLY LABEL 1"X.5" 500/RL

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[596-00183](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00183



Article Number: 596-00183

Thermal Transfer Label, 2.5" X .5", For Use On White Insert 596-00420, PET, White, 500/RL



Download spec sheet

## Base Data

Local Order Number 596-00183

Type NPL63X13

Color White (WH)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
  - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
  - Labels are UV and chemical resistant for long life in an industrial environment.
  - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Product Description** Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

**Short Description** Thermal Transfer Label, 2.5" X .5", For Use On White Insert 596-00420, PET, White, 500/RL

## Product Dimensions

Length L (Imperial) 0.5 "

Length L (Metric) 12.7 mm

Self adhesive (Yes/No) Yes

Width W (Imperial) 2.50 "

Width W (Metric) 63.5 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Horizontal Repeat HR (imperial) 2.5 "

Horizontal Repeat HR (metric) 63.5 mm

Print Method Thermal Transfer

Vertical Repeat VR (metric) 15.8 mm

Vertical Repeat VR (imperial) 0.625 "

Width of Liner WL (metric) 66.67 mm

Width of Liner WL (imperial) 2.625 "

## Logistics and Packaging

Quantity Per reel

Package Quantity 500



**Package Quantity (Metric)** 500

**Labels per Column** 1

**Labels per Row** 1

## Material and Specifications

---

**Material** Polyester (PET)

**Material Shortcut** PET

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**ROHS Compliant** Yes