



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 596-00202 - LABEL ID/RATING 2.37"X2.37" YLLW

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[596-00202](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00202

Article Number: 596-00202

Foam Nameplate, 2.375" X 2.375" Emergency Stop label, PET, Yellow, 100/RL



Download spec sheet

## Base Data

Local Order Number 596-00202

Type NPL60X60YE

Color Yellow (YE)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
  - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
  - Labels are UV and chemical resistant for long life in an industrial environment.
  - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Product Description** The Pre-printed colored header vinyl rolls can be used to design signs that conform to Occupational Safety and Hazard Association (OSHA) and American National Standards Institute (ANSI) requirements for Warning and Caution Signs and markers. All can be designed, printed and cut to length in Tagprint Pro and any HellermannTyton thermal transfer printing system.

**Short Description** Foam Nameplate, 2.375" X 2.375" Emergency Stop label, PET, Yellow, 100/RL

## Product Dimensions

Length L (Imperial) 2.375 "

Length L (Metric) 60.3 mm

Self adhesive (Yes/No) Yes

Width W (Imperial) 2.375 "

Width W (Metric) 60.3 mm

Height H (Imperial) 2.375 "

Height H (Metric) 60.3 mm

Mounting Hole Diameter D (Imperial) 1.20 "

Mounting Hole Diameter D (Metric) 30.48 mm

Horizontal Repeat HR (metric) 66.6 mm

Horizontal Repeat HR (imperial) 2.625 "

Mounting Hole Diameter D Max. (Metric) 30.48 mm

Mounting Hole Diameter D Min. (Metric) 30.48 mm

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 2.375 "

Vertical Repeat VR (metric) 60 mm

Width of Liner WL (imperial) 2.55 "

Width of Liner WL (metric) 64.77 mm



## Logistics and Packaging

---

Quantity Per	reel
Package Quantity	100
Package Quantity (Metric)	100

## Material and Specifications

---

Material	Polyester (PET)
Material Shortcut	PET
Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +176°F (-40°C to +80°C)
Operating Temperature	-40°F to +176°F (-40°C to +80°C)
ROHS Compliant	Yes
UL Recognized (US)	Yes