



## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[596-00253](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00253

Article Number: 596-00253

Printable Solar Label, DC Module Label, 4.0" X 2.0", Polyester, Red, 50/RL



Download spec sheet

## Base Data

Local Order Number 596-00253

Type DC2011

Color Red (RD)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance.
  - The labels are supplied with aggressive adhesive to ensure long life.
  - Solar Installation labels meet NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Technical Description** 4" X2" White text on red background that reads as: "RATED MAX POWER-POINT CURRENT;RATED MAX POWER-POINT CURRENT;MAXIMUM SYSTEM VOLTAGE;MAXIMUM CIRCUIT CURRENT;MAX RATED OUTPUT CURRENT OF THE CHARGE CONTROLLER (IF INSTALLED)." 50 per roll. Label is also printable using a thermal transfer printer to add the variable voltage information on demand.

Local Order Number 2 Spanish Version: 596-00817

Short Description Printable Solar Label, DC Module Label, 4.0" X2.0", Polyester, Red, 50/RL

## Product Dimensions

Length L (Imperial)	4.0 "
Length L (Metric)	101.6 mm
Width W (Imperial)	4.0 "
Width W (Metric)	101.6 mm
Height H (Imperial)	2.0 "
Height H (Metric)	50.8 mm

## Logistics and Packaging

Quantity Per	roll
Package Quantity	50
Package Quantity (Metric)	50
Labels per Column	1
Labels per Row	1

## Material and Specifications

**Material Shortcut** 840/926

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +180°F (-40°C to +82°C)

**Halogenfree** Yes

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**ROHS Compliant** Yes

**Certification/Specification** UL969

**UL Recognized (US)** Yes