

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[596-00418](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## 596-00418



**Article Number:** 596-00418

Insert for 596-00189, 596-00190, 596-00191, 1.06" X .59", Plastic, White, 360/pkg



Download spec sheet

### Base Data

**Local Order Number** 596-00418

**Type** WPL15X27

**Color** White (WH)

- Features and Benefits**
- The legend base inserts are made of high performance polycarbonate.
  - The inserts can be marked with a standard label or if a plotter is available, can be printed with ink jet or laser etching.
  - The inserts snap easily into the plastic legend bases for a high contrast and permanent identifier.

**Product Description** Plastic Nameplate labels are less costly than plastic or metal engraved plates, saving material costs. Plastic Nameplate labels are made of a UL94VO rated polycarbonate that can be mounted mechanically or using an adhesive backing. HellermannTyton thermal transfer or laser labels can be printed and applied to the inserts and covered with a clear plastic cover to protect printed text.

**Short Description** Insert for 596-00189, 596-00190, 596-00191, 1.06" X .59", Plastic, White, 360/pkg

### Product Dimensions

**Self adhesive (Yes/No)** Yes

**Width W (Imperial)** 1.06 "

**Width W (Metric)** 27 mm

**Height H (Imperial)** 0.59 "

**Height H (Metric)** 15 mm

**Horizontal Repeat HR (imperial)** 1.06 "

**Horizontal Repeat HR (metric)** 27 mm

**Print Method** Thermal Transfer

**Vertical Repeat VR (metric)** 15 mm

**Vertical Repeat VR (imperial)** 0.59 "

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 360

**Package Quantity (Metric)** 360

**Labels per Column** 4

**Labels per Row** 3

### Material and Specifications

**Material** Polycarbonate (PC)



**Adhesive Shortcut** Acrylic

**Flammability** UL94 V0

**Operating Temperature** -22°F to +266°F (-30°C to +130°C)

**ROHS Compliant** Yes