

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[596-00500](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00500

Article Number: 596-00500

Foam Nameplate, 1.06" X .49" Rectangular Nameplate, PET, White, 500/RL



Download drawing



Download spec sheet

## Base Data

Local Order Number 596-00500

Type NPL27X13WH

Color White (WH)

- Features and Benefits**
- Foam Nameplate labels are less costly than plastic or metal engraved plates, saving material costs.
  - Foam Nameplate labels conform to textured and other low energy surfaces ensuring the labels stay in place for the life of the product.
  - Labels are UV and chemical resistant for long life in an industrial environment.
  - Foam nameplate labels are printable using a thermal transfer printer for complete control and on-demand creation of labels.

**Product Description** Foam Nameplate labels are designed to replace plastic and metal engraved phenolic plates commonly found on electrical control panels. The labels provide the look and feel of a plastic engraved or metal plate, but at a fraction of the cost. Labels can be printed using HellermannTyton Tagprint Pro labeling software and can include printed logos, barcodes and text of almost any size and type.

**Short Description** Foam Nameplate, 1.06" X .49" Rectangular Nameplate, PET, White, 500/RL

## Product Dimensions

Length L (Imperial) 0.49 "

Length L (Metric) 12.4 mm

Self adhesive (Yes/No) Yes

Width W (Imperial) 1.06 "

Width W (Metric) 27.0 mm

Height H (Imperial) 0.49 "

Height H (Metric) 12.4 mm

Horizontal Repeat HR (imperial) 1.06 "

Horizontal Repeat HR (metric) 27 mm

Print Method Thermal Transfer

Width of Liner WL (metric) 32 mm

Width of Liner WL (imperial) 1.25 "

## Logistics and Packaging

Quantity Per reel

Package Quantity 500

Package Quantity (Metric) 500

Weight (Metric) 0.22 kg

Weight (imperial) 0.5 lbs



## Material and Specifications

---

<b>Material</b>	Polyester (PET)
<b>Material Shortcut</b>	PET
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>Operating Temperature</b>	-40°F to +176°F (-40°C to +80°C)
<b>ROHS Compliant</b>	Yes
<b>UL Recognized (US)</b>	Yes