

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[FC2.2AK2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

FC2.2AK2



Article Number: 154-00017

Flat Ribbon Adhesive Clamp, 2.2" Max Cable Width, 0.156" Hole Dia., PA66, Gray, 50/pkg



Download spec sheet

Base Data

Local Order Number FC2.2AK2

Type FC2.2A

Color Gray (GY)

Features and Benefits

- Adjustable height feature allows the clamp to close to the exact height of the ribbon cable.
- Releasable for easy access to cables when necessary.
- Available in adhesive or screw mount versions.

Product Description HellermannTyton's flat ribbon clamps route, protect and secure flat ribbon cables without damage to sensitive wires and cables. The unique, adjustable height feature allows the clamp to close to the exact height of the ribbon cable, using only as much force as needed to secure the cable. The releasable feature allows simple opening when access to the cable is necessary. These clamps are available in adhesive or screw mount versions.

Short Description Flat Ribbon Adhesive Clamp, 2.2" Max Cable Width, 0.156" Hole Dia., PA66, Gray, 50/pkg

Product Dimensions

Length L (Imperial) 0.75 "

Length L (Metric) 19.0 mm

Width W (Imperial) 2.6 "

Width W (Metric) 66.0 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Mounting Hole Diameter D (Imperial) 0.156 "

Mounting Hole Diameter D (Metric) 4.0 mm

For Cable Width Max. (Metric) 55.9 mm

For Cable Width Max. (Imperial) 2.2 "

Mounting Hole Diameter D Max. 4.0 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 4.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 50

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Adhesive Acrylate with base of polyurethane foam

Adhesive Operating Temperature to +230°F (+110°C)

Flammability UL94 V2 (excluding adhesive)

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes