

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[FC2.2K2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

FC2.2K2



Article Number: 154-00015

Flat Ribbon Clamp, 2.2" Max Cable Width, 0.156" Hole Dia., PA66, Gray, 50/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number FC2.2K2

Type FC2.2

Color Gray (GY)

Features and Benefits

- Adjustable height feature allows the clamp to close to the exact height of the ribbon cable.
- Releasable for easy access to cables when necessary.
- Available in adhesive or screw mount versions.

Product Description HellermannTyton's flat ribbon clamps route, protect and secure flat ribbon cables without damage to sensitive wires and cables. The unique, adjustable height feature allows the clamp to close to the exact height of the ribbon cable, using only as much force as needed to secure the cable. The releasable feature allows simple opening when access to the cable is necessary. These clamps are available in adhesive or screw mount versions.

Short Description Flat Ribbon Clamp, 2.2" Max Cable Width, 0.156" Hole Dia., PA66, Gray, 50/pkg

Product Dimensions

Length L (Imperial) 0.75 "

Length L (Metric) 19.0 mm

Width W (Imperial) 2.6 "

Width W (Metric) 66.0 mm

Width W2 (Imperial) 1.5 "

Width W2 (Metric) 38.1 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Mounting Hole Diameter D (Imperial) 0.156 "

Mounting Hole Diameter D (Metric) 4.0 mm

For Cable Width Max. (Metric) 55.9 mm

For Cable Width Max. (Imperial) 2.2 "

Mounting Hole Diameter D Max. (Metric) 4.0 mm

Mounting Hole Diameter D Min. (Metric) 4.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 50

Material and Specifications



Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes