

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[MB4SH10H4](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

MB4SH10H4



Article Number: 151-00323

Screw Fastened Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, White, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number MB4SH10H4

Type MB4SH

Color White (WH)

Features and Benefits

- For use with 18 through 50 pound cable ties to provide stability when securing bundles.
- Secures with one screw, for easy installation.

Product Description HellermannTyton's 2 way, screw fastened mounting base is used with 18 through 50 pound cable ties to provide stability when securing bundles. The mounts are installed by securing one screw through the center of the mount.

Short Description Screw Fastened Bases, .18" Max tie width, .15" Hole Dia., 1.12" Length/Width, PA66, White, 500/pkg

Product Dimensions

Length L (Imperial) 1.12 "

Length L (Metric) 28.3 mm

Fixation Method Screw Mounting and Rivet

Width W (Imperial) 1.12 "

Width W (Metric) 28.3 mm

Cable Tie Width Max. (Imperial) 0.18 "

Cable Tie Width Max. (Metric) 4.6 mm

Height H (Imperial) 0.2 "

Height H (Metric) 5.1 mm

Mounting Hole Diameter D (Imperial) 0.15 "

Mounting Hole Diameter D (Metric) 3.9 mm

Mounting Hole Diameter D Max. 3.9 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 3.9 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of MB4SH10H4 - CABLE TIE MOUNT 1.115"X1.115"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

ROHS Compliant Yes

Certification/Specification UL

UL Listed (US and Canada) No

UL Recognized (US and Canada) Yes