

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[MMB10H4](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

MMB10H4



Article Number: 151-00327

Masonry Mount, 1.712" Length, .312" Hole Dia., .18" Max. Cable Tie Width, PA46, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number MMB10H4

Type MMB1

Color Black (BK)

Features and Benefits

- Masonry Mounts provides a permanent solution when fastening wire and cables to masonry surfaces.
- The mounts have easy installation into predrilled holes allowing for faster use.

Product Description HellermannTyton masonry mounts provide a permanent mounting solution when fastening wire and cables to masonry surfaces. Designed for easy installation by simply tapping into predrilled holes.

Short Description Masonry Mount, 1.712" Length, .312" Hole Dia., .18" Max. Cable Tie Width, PA46, Black, 500/pkg

Product Dimensions

Length L (Imperial) 1.712 "

Length L (Metric) 43.5 mm

Fixation Method with Fir Tree (Mounts)

Width W (Imperial) 0.508 "

Width W (Metric) 12.9 mm

Cable Tie Width Max. (Imperial) 0.18 "

Cable Tie Width Max. (Metric) 4.6 mm

Width W2 (Imperial) 0.374 "

Width W2 (Metric) 9.5 mm

Width W3 (Imperial) 0.362 "

Width W3 (Metric) 9.2 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Mounting Hole Diameter D (Imperial) 0.312 "

Mounting Hole Diameter D (Metric) 8.0 mm

Mounting Hole Diameter D Max. 8.0 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 8.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Carton Quantity 4000

Material Polyamide 4.6 (PA46)

Material Shortcut PA46

Flammability UL94 V2

Operating Temperature -40°F to +275°F (-40°C to +135°C)

ROHS Compliant Yes