

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[SNP1.5GHS0C2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## SNP1.5GHS0C2



Article Number: 190-00251

Snapper Hose Clamps, .315"/.35" Min/Max Diameter, PA66GF13%, Black, 100/pkg



Download spec sheet

### Base Data

Local Order Number SNP1.5GHS0C2

Type SNP1.5

Color Black (BK)

**Features and Benefits**

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

**Product Description** HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

**Short Description** Snapper Hose Clamps, .315"/.35" Min/Max Diameter, PA66GF13%, Black, 100/pkg

### Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.147 "

Width W2 (Metric) 3.73 mm

Bundle Diameter Min. (Imperial) 0.32 "

Bundle Diameter Min. (Metric) 8.0 mm

Bundle Diameter Max. (Imperial) 0.36 "

Bundle Diameter Max. (Metric) 9 mm

Diameter Min. (Imperial) 0.315 "

Diameter Min. (Metric) 8.0 mm

Diameter Max. (Imperial) 0.35 "

Diameter Max. (Metric) 8.89 mm

Wall Thickness WT (Imperial) 0.055 "

Wall Thickness WT (Metric) 1.414 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 15000

Weight (Metric) 0.5 kg

### Material and Specifications



**Material Shortcut** PA66GF13

**Flammability** UL94 HB

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes