

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[SNP19GHS0C2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

SNP19GHS0C2



Article Number: 190-00090

Snapper Hose Clamps, .961"/.966" Min/Max Diameter, PA66GF13%, Black, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number SNP19GHS0C2

Type SNP19

Color Black (BK)

Features and Benefits

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

Product Description HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

Short Description Snapper Hose Clamps, .961"/.966" Min/Max Diameter, PA66GF13%, Black, 100/pkg

Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.232 "

Width W2 (Metric) 5.89 mm

Bundle Diameter Min. (Imperial) 0.88 "

Bundle Diameter Min. (Metric) 22.3 mm

Bundle Diameter Max. (Imperial) 0.99 "

Bundle Diameter Max. (Metric) 25.3 mm

Diameter Min. (Imperial) 0.961 "

Diameter Min. (Metric) 24.41 mm

Diameter Max. (Imperial) 0.996 "

Diameter Max. (Metric) 25.3 mm

Nominal Diameter (Imperial) 15/16 "

Nominal Diameter (Metric) 23 mm

Wall Thickness WT (Imperial) 0.071 "

Wall Thickness WT (Metric) 1.8 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 2000



Material Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)

Material Shortcut PA66GF13

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes