

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[SNP38GHS0K2](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## SNP38GHS0K2



Article Number: 192-10380

Snapper Hose Clamps, 1.614"/1.894" Min/Max Diameter, PA66GF13%, Black, 50/pkg



Download drawing



Download spec sheet

### Base Data

Local Order Number SNP38GHS0K2

Type SNP38

Color Black (BK)

**Features and Benefits**

- Designed for quick, ratcheted installation and can be released and reused.
- Heat stabilized material is suitable for high temperature applications.

**Product Description** HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

**Short Description** Snapper Hose Clamps, 1.614"/1.894" Min/Max Diameter, PA66GF13%, Black, 50/pkg

### Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.287 "

Width W2 (Metric) 7.29 mm

Bundle Diameter Min. (Imperial) 1.61 "

Bundle Diameter Min. (Metric) 41.0 mm

Bundle Diameter Max. (Imperial) 1.88 "

Bundle Diameter Max. (Metric) 48.1 mm

Diameter Min. (Imperial) 1.614 "

Diameter Min. (Metric) 41.0 mm

Diameter Max. (Imperial) 1.894 "

Diameter Max. (Metric) 48.11 mm

Nominal Diameter (Imperial) 1-3/4 "

Nominal Diameter (Metric) 45 mm

Wall Thickness WT (Imperial) 0.069 "

Wall Thickness WT (Metric) 1.8 mm

### Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 50 Pieces

Weight (Metric) 0.42 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 glass filled impact modified heat stabilized (PA66GF13%)
<b>Material Shortcut</b>	PA66GF13
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes