

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[SNP7610C2](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

SNP7610C2



Article Number: 190-00217

Snapper Hose Clamps, 2.85"/3.171" Min/Max Diameter, POM, White, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number SNP7610C2

Type SNP76

Color White (WH)

Features and Benefits

- Designed for quick, ratcheted installation and can be released and reused.
- Polyacetal material resists chemicals, corrosion and UV rays making it suitable for extreme environments.

Product Description HellermannTyton snapper hose clamps are designed to provide a quick, ratcheted closure reducing installation time. The design also allows the clamp to be easily removed and re-applied when necessary. Snappers are made of high performing materials providing stability in a variety of diverse environments. Available in 32 standard sizes.

Short Description Snapper Hose Clamps, 2.85"/3.171" Min/Max Diameter, POM, White, 100/pkg

Product Dimensions

Fixation Method Plug-in mounting

Variant Closed

Width W2 (Imperial) 0.385 "

Width W2 (Metric) 9.78 mm

Bundle Diameter Min. (Imperial) 2.85 "

Bundle Diameter Min. (Metric) 72.5 mm

Bundle Diameter Max. (Imperial) 3.2 "

Bundle Diameter Max. (Metric) 80.5 mm

Diameter Min. (Imperial) 2.85 "

Diameter Min. (Metric) 72.39 mm

Diameter Max. (Imperial) 3.171 "

Diameter Max. (Metric) 80.54 mm

Wall Thickness WT (Imperial) 0.066 "

Wall Thickness WT (Metric) 1.7 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

Carton Quantity 400

Material and Specifications

Material Polyacetal (POM)



Distributor of HellemanTyton: Excellent Integrated System Limited

Datasheet of SNP7610C2 - SNPPR HOSE CLAMP MAX 3.206"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Flammability UL94 HB

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes