

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T3D018710M4](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

T3D018710M4



Article Number: 211-00158

P Clamp, .375" Width, .188" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T3D018710M4

Type T3D0187

Color White (WH)

Features and Benefits

- P-Clamps easily guide and locate wire and cables up to 0.625" in diameter.
- Designed with a radiused edge to prevent chaffing and cutting into insulation.

Product Description HellermannTyton P Clamps easily guide and locate wires and cables. The clamps are designed with a radiused edge to prevent chaffing and cutting into insulation. Available sizes up to 1" bundle diameters.

Short Description P Clamp, .375" Width, .188" Max Bundle Dia, .203" Mounting Hole Dia, PA66, White, 1000/pkg

Product Dimensions

Fixation Method screw-hole

Variant Closed

Width W (Imperial) 0.375 "

Width W (Metric) 9.53 mm

Bundle Diameter Max. (Imperial) 0.188 "

Bundle Diameter Max. (Metric) 4.78 mm

Mounting Hole Diameter D (Imperial) 0.203 "

Mounting Hole Diameter D (Metric) 5.1 mm

Wall Thickness WT (Imperial) .050 "

Wall Thickness WT (Metric) 1.3 mm

Mounting Hole Centers (Imperial) 0.43 "

Mounting Hole Diameter D Max. 5.1 mm

(Metric) Mounting Hole Diameter D Min. (Metric) 5.1 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 1000 Pieces

Material and Specifications

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of T3D018710M4 - T CLAMP-T3 SERIES .375"

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

ROHS Compliant Yes

UL Recognized (US and Canada) Yes