

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[T50R9PPC2](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

T50R9PPC2



Article Number: 111-04931

High Temp Tie, 8" Long, 25lb Tensile Strength, PP, Natural, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number T50R9PPC2

Type T50R

Color Natural (NA)

- Features and Benefits**
- Polypropylene cable ties provide excellent resistance to chemicals and salts.
 - Inside serrations allow for strong hold on cables and wire bundles.
 - Head design provides high tensile strength with very low insertion force.
 - Bent tail ensures a quick and simple installation.

Product Description HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

Short Description High Temp Tie, 8" Long, 25lb Tensile Strength, PP, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 25.0 lbs

Minimum Tensile Strength (Metric) 111.0 N

Length L (Imperial) 8.0 "

Length L (Metric) 202.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.8 mm

Bundle Diameter Min. (Imperial) 0.5 "

Bundle Diameter Min. (Metric) 12.7 mm

Bundle Diameter Max. (Imperial) 1.75 "

Bundle Diameter Max. (Metric) 44.5 mm

Thickness T (Imperial) 0.05 "

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity Per bag

Carton Quantity 5000

Material and Specifications

Material Polypropylene (PP)

Material Shortcut PP

Flammability UL94 HB

Halogenfree Yes

Operating Temperature -40°F to +239°F (-40°C to +115°C)

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Recognized (US and Canada) No