

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[T50RSF9M4](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## T50RSF9M4



Article Number: 126-01011

Push Mount Tie, 8.3" Long, 50lb Tensile, Panel Thickness .25"- .28", PA66, Natural, 1,000/pkg



Download drawing



Download spec sheet

### Base Data

Local Order Number T50RSF9M4

Type T50RSF(U)

Color Natural (NA)

- Features and Benefits**
- Push Mount design creates quick and easy mounting for installers.
  - Push mount style creates low insertion and high extraction force.
  - Ties "clicks" into place upon final installation signaling installer insertion is complete.

**Product Description** Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

**Short Description** Push Mount Tie, 8.3" Long, 50lb Tensile, Panel Thickness .25"- .28", PA66, Natural, 1,000/pkg

### Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 8.3 "

Length L (Metric) 210.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Height H (Imperial) 0.3 "

Height H (Metric) 7.5 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.6 mm

Bundle Diameter Max. (Imperial) 1.7 "

Bundle Diameter Max. (Metric) 44.0 mm

Panel Thickness Max. (Imperial) 0.14 "

Panel Thickness Max. (Metric) 3.56 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 1.00 mm

Mounting Hole Diameter D (Imperial) 0.25 - 0.28 "

Mounting Hole Diameter D (Metric) 6.4 - 7.1 mm

<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.25 "	<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.28 "	<b>Thickness T (Imperial)</b>	0.05 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	7.1 mm	<b>Mounting Hole Diameter D Min. (Metric)</b>	6.4 mm		
<b>Thickness T (Metric)</b>	1.2 mm				

---

### Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	1000
<b>Carton Quantity</b>	5000

---

### Material and Specifications

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL
<b>UL Listed (US and Canada)</b>	No
<b>UL Recognized (US and Canada)</b>	Yes