

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TAG15T3-822](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TAG15T3-822

Article Number: 596-15822

Thermal Transfer Label, 1.0" X .5", 3 Across, Polyester, White, 10000/RL



Download drawing



Download spec sheet

Base Data

Local Order Number TAG15T3-822

Type TAG15T3

Color White (WH)

- Features and Benefits**
- Thermal transfer labels are made with high performance materials for long term industrial applications.
 - Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.
 - The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.

Product Description Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.

Short Description Thermal Transfer Label, 1.0" X .5", 3 Across, Polyester, White, 10000/RL

Product Dimensions

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Height H (Imperial) 0.50 "

Height H (Metric) 12.7 mm

Horizontal Repeat HR (metric) 25.4 mm

Horizontal Repeat HR (imperial) 1.0 "

Print Method Thermal Transfer

Vertical Repeat VR (metric) 15.24 mm

Vertical Repeat VR (imperial) 0.60 "

Width of Liner WL (imperial) 3.35 "

Width of Liner WL (metric) 85.09 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 10000

Package Quantity (Metric) 10000

Carton Quantity 10000 Pieces

Labels per Row 3

Weight (Metric) 0.816 kg

Material	Type 822, Polyester, white (WH)
Material Shortcut	822
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS Compliant	Yes
Certification/Specification	UL-Recognized
UL Recognized (US and Canada)	Yes