

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAG16-400](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAG16-400

Article Number: 595-16400

Dot Matrix Label, .90" X .25", 8 Across, Polyester, White, 5000/pkg



Download spec sheet

### Base Data

Local Order Number TAG16-400

Type TAG16

Color White (WH)

**Features and Benefits**

- Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

**Product Description** Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.

**Short Description** Dot Matrix Label, .90" X .25", 8 Across, Polyester, White, 5000/pkg

### Product Dimensions

Length L (Imperial) 0.25 "

Length L (Metric) 6.4 mm

Width W (Imperial) 0.9 "

Width W (Metric) 22.8 mm

Height H (Imperial) 0.25 "

Height H (Metric) 6.35 mm

Height of printable area (metric) 6.40 mm

Horizontal Repeat HR (imperial) 1.000 "

Horizontal Repeat HR (metric) 25.40 mm

Print Method Dot-Matrix

Vertical Repeat VR (imperial) 0.333 "

Vertical Repeat VR (metric) 8.45 mm

Width of Liner WL (imperial) 8.9 "

Width of Liner WL (metric) 226.00 mm

### Logistics and Packaging

Quantity Per pack

Package Quantity 5000

Package Quantity (Metric) 5000

Carton Quantity 5000 Pieces

Labels per Row 8

## Material and Specifications

---

|                                       |                                   |
|---------------------------------------|-----------------------------------|
| <b>Material</b>                       | Type 400, Polyester, white (WH)   |
| <b>Material Shortcut</b>              | 400                               |
| <b>Adhesive</b>                       | Acrylic                           |
| <b>Adhesive Shortcut</b>              | Acrylic                           |
| <b>Adhesive Operating Temperature</b> | -40°F to +302°F (-40°C to +150°C) |
| <b>Operating Temperature</b>          | -40°F to +302°F (-40°C to +150°C) |
| <b>ROHS Compliant</b>                 | Yes                               |
| <b>Certification/Specification</b>    | UL-Recognized                     |