

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAG22J-994](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAG22J-994

Article Number: 593-22994

Ink Jet Self-Laminating Label, 1.0" X .5" X 1.625", 32 Per Sheet, Polyester, White, 1000/pkg



Download spec sheet

### Base Data

**Local Order Number** TAG22J-994

**Type** TAG22J

**Color** White (WH)

- Features and Benefits**
- HellermannTyton Ink Jet labels are sheet fed for easy loading and fast printing.
  - Ink Jet labels are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
  - Ink Jet labels are printable using toner for long term UV exposure.
  - Ink Jet labels come in a variety of label sizes and types to fit most applications.

**Color Marking Field** White (WH)

**Product Description** Ink Jet labels are durable, ink jet printable markers for applications requiring clear, crisp legibility. The labels are supplied on sheets and are printable using HellermannTyton Tagprint Pro software and a standard ink jet printer. Specially designed adhesives and topcoats accept the ink allowing for easy color printing for specific applications that require colors.

**Short Description** Ink Jet Self-Laminating Label, 1.0" X .5" X 1.625", 32 Per Sheet, Polyester, White, 1000/pkg

### Product Dimensions

**Length L (Imperial)** 1.43 "

**Length L (Metric)** 36.32 mm

**Width W (Imperial)** 1.0 "

**Width W (Metric)** 25.4 mm

**Height H (Imperial)** 0.50 "

**Height H (Metric)** 12.7 mm

**Height H2 (Imperial)** 1.43 "

**Height H2 (Metric)** 36.5 mm

**Height of printable area (imperial)** 0.50 "

**Height of printable area (metric)** 12.70 mm

**Bundle Diameter Min. (Imperial)** 0.15 "

**Bundle Diameter Min. (Metric)** 3.80 mm

**Bundle Diameter Max. (Imperial)** 0.32 "

**Bundle Diameter Max. (Metric)** 8.00 mm

**Outside Diameter Min. (Imperial)** 0.15 "

**Outside Diameter Min. (Metric)** 3.8 mm

**Outside Diameter Max. (Imperial)** 0.315 "

**Outside Diameter Max. (Metric)** 8.00 mm

<b>Horizontal Repeat HR (metric)</b>	25.40 mm
<b>Print Method</b>	Inkjet
<b>Thickness T (Metric)</b>	35.0 µm
<b>Vertical Repeat VR (imperial)</b>	1.43 "
<b>Vertical Repeat VR (metric)</b>	36.32 mm
<b>Width of Liner WL (imperial)</b>	8.5 "
<b>Width of Liner WL (metric)</b>	215.00 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	pack
<b>Package Quantity</b>	1000
<b>Package Quantity (Metric)</b>	1000
<b>Carton Quantity</b>	1000
<b>Labels per Column</b>	4
<b>Labels per Row</b>	8
<b>Labels per Sheet</b>	32

## Material and Specifications

---

<b>Material</b>	Type 994, Polyethylenterephthalat (PET)
<b>Material Shortcut</b>	994
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>ROHS Compliant</b>	Yes