

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAG24-100](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAG24-100

Article Number: 595-24100

Dot Matrix, Self-Laminating Label, 2.0" X .50" X 1.437", 4 Across, White, 5000/pkg



Download spec sheet

### Base Data

Local Order Number TAG24-100

Type TAG24

Color White (WH)

**Features and Benefits**

- Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

Color Marking Field White (WH)

**Product Description** Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.

Mounting method Identification ETIM Pasting / Stick

Short Description Dot Matrix, Self-Laminating Label, 2.0" X .50" X 1.437", 4 Across, White, 5000/pkg

### Product Dimensions

Length L (Imperial) 1.437 "

Length L (Metric) 36.5 mm

Self adhesive (Yes/No) Yes

Variant Adhesive label

Width W (Imperial) 2.0 "

Width W (Metric) 50.8 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Height H2 (Imperial) 1.437 "

Height H2 (Metric) 36.5 mm

Height of printable area (metric) 12.70 mm

Bundle Diameter Min. (Imperial) 0.14 "

Bundle Diameter Min. (Metric) 3.80 mm

Bundle Diameter Max. (Imperial) 0.29 "

Bundle Diameter Max. (Metric) 7.60 mm

Outside Diameter Min. (Imperial) 0.14 "

Outside Diameter Min. (Metric) 3.8 mm

Outside Diameter Max. (Imperial) 0.29 "

Outside Diameter Max. (Metric) 7.60 mm

<b>Horizontal Repeat HR (imperial)</b>	2.000 "
<b>Print Method</b>	Dot-Matrix
<b>Thickness T (Metric)</b>	75.0 µm
<b>Vertical Repeat VR (imperial)</b>	1.5 "
<b>Vertical Repeat VR (metric)</b>	38.10 mm
<b>Width of Liner WL (imperial)</b>	8.9 "
<b>Width of Liner WL (metric)</b>	228.60 mm

---

## Logistics and Packaging

<b>Quantity Per</b>	pack
<b>Package Quantity (Metric)</b>	5000
<b>Carton Quantity</b>	5000 Pieces
<b>Labels per Column</b>	4
<b>Labels per Row</b>	4
<b>Weight (Metric)</b>	0.46 kg

---

## Material and Specifications

<b>Material</b>	Type 100, Vinyl (PVC), white (WH), self laminating
<b>Material Shortcut</b>	100
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-51°F to +200°F (-46°C to +93°C)
<b>Operating Temperature</b>	-51°F to +200°F (-46°C to +93°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-Recognized