

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAG27-600](#)

For any questions, you can email us directly:  
[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAG27-600

**Article Number:** 595-27600

**Dot Matrix Label, 1.5" X .75", 4 Across, Metalized Polyester, Silver, 5000/pkg**



Download spec sheet

### Base Data

**Local Order Number** TAG27-600

**Type** TAG27

**Color** Silver (SR)

**Features and Benefits**

- Tabtag Dot Matrix labels are specifically made for use in dot matrix printers for fast and easy printing.
- Labels come with a pin-feed margin to ensure that they can easily be loaded into any dot matrix printing system.

**Product Description** Used with dot matrix printers, HellermannTyton TabTags can be used for virtually any labeling application. Unless noted, TabTags are mounted on pinfed, fan-folded sheets for use with computers, word processors, or typewriters. Manufactured in a wide range of standard sizes and materials, the dot matrix printable TabTags can meet a wide variety of labeling requirements.

**Short Description** Dot Matrix Label, 1.5" X .75", 4 Across, Metalized Polyester, Silver, 5000/pkg

### Product Dimensions

**Length L (Imperial)** 0.75 "

**Length L (Metric)** 19.0 mm

**Width W (Imperial)** 1.5 "

**Width W (Metric)** 38.1 mm

**Height H (Imperial)** 0.75 "

**Height H (Metric)** 19.05 mm

**Height of printable area (metric)** 19.00 mm

**Horizontal Repeat HR (metric)** 43.18 mm

**Horizontal Repeat HR (imperial)** 1.700 "

**Print Method** Dot-Matrix

**Vertical Repeat VR (metric)** 25.40 mm

**Vertical Repeat VR (imperial)** 1.0 "

**Width of Liner WL (imperial)** 7.625 "

**Width of Liner WL (metric)** 193.70 mm

### Logistics and Packaging

**Quantity Per** pack

**Package Quantity** 5000

**Package Quantity (Metric)** 5000

**Carton Quantity** 5000 Pieces

**Labels per Row** 4

## Material and Specifications

---

<b>Material</b>	Type 600, Polyester, silver-matt (SR)
<b>Material Shortcut</b>	600
<b>Adhesive Shortcut</b>	Acrylic
<b>Adhesive</b>	Acrylic
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL-Recognized