

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TAG68L-789](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TAG68L-789

Article Number: 594-68789

Laser Tag Label, 3.8" X .275", 70 Per sheet, Polyester, White, 1000/pkg



Download spec sheet

Base Data

Local Order Number TAG68L-789

Type TAG68L

Color White (WH)

- Features and Benefits**
- LaserTags are sheet fed for easy loading and fast printing.
 - LaserTags are made with high temperature materials and adhesives so that they will not be affected by the high heat of laser printing.
 - LaserTags are printable using toner for long term UV exposure.
 - LaserTags come in a variety of label sizes and types to fit most applications.

Product Description LaserTags are durable, laser printable labels for applications requiring clear, crisp legibility. The labels are supplied on 8.5" X 11" sheets and are printable using HellermannTyton Tagprint Pro software and a standard laser printer. Specially designed adhesives and materials are used for the LaserTags, ensuring that the labels will not curl, change color, or jam standard laser printers.

Short Description Laser Tag Label, 3.8" X .275", 70 Per sheet, Polyester, White, 1000/pkg

Product Dimensions

Length L (Imperial) 0.275 "

Length L (Metric) 6.98 mm

Width W (Imperial) 3.80 "

Width W (Metric) 96.5 mm

Height H (Imperial) 0.275 "

Height H (Metric) 6.98 mm

Height of printable area (imperial) 0.275 "

Height of printable area (metric) 6.98 mm

Horizontal Repeat HR (metric) 96.50 mm

Horizontal Repeat HR (imperial) 3.800 "

Print Method Laser

Thickness T (Metric) 64.0 µm

Vertical Repeat VR (imperial) 0.275 "

Vertical Repeat VR (metric) 6.98 mm

Logistics and Packaging

Quantity Per pack

Package Quantity 2500

Package Quantity (Metric) 2500



Labels per Column 35

Labels per Row 2

Labels per Sheet 70

Material and Specifications

Material Type 789, Polyethylenterephthalat (PET)

Material Shortcut 789

Adhesive Acrylic

Adhesive Shortcut Acrylic

Operating Temperature -40°F to +302°F (-40°C to +150°C)

ROHS Compliant Yes