

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[TAG6T1-100B](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

## TAG6T1-100B

Article Number: 596-00016

Thermal Transfer Self-Laminating Label, 2.0" X 1.0" X 3.75", 1 Across, Vinyl, White, 1000/RL



Download drawing



Download spec sheet

### Base Data

**Local Order Number** TAG6T1-100B

**Type** TAG6T1

**Color** White (WH)

- Features and Benefits**
- Clear laminate provides excellent abrasion protection and chemical resistance.
  - Flexible material bends around small gauge wires and tight bends.
  - Labels are UL recognized and include a strong acrylic adhesive for indoor and outdoor use.
  - Standard 3" core can be used with HellermannTyton thermal transfer printers or most standard brands.

**Color Marking Field** White (WH)

**Product Description** HellermannTyton self-laminating thermal transfer printer labels are made of a flexible vinyl film with a white printable surface that easily conforms to wires. These labels include a clear "tail" that laminates printed text when applied. Labels are UL recognized for indoor and outdoor use and feature a strong acrylic adhesive designed to bond to both large and small diameter wires.

**Short Description** Thermal Transfer Self-Laminating Label, 2.0" X 1.0" X 3.75", 1 Across, Vinyl, White, 1000/RL

### Product Dimensions

**Length L (Imperial)** 3.75 "

**Length L (Metric)** 95.25 mm

**Width W (Imperial)** 2.0 "

**Width W (Metric)** 50.8 mm

**Height H (Imperial)** 3.75 "

**Height H (Metric)** 95.25 mm

**Height H2 (Imperial)** 3.75 "

**Height H2 (Metric)** 95.25 mm

**Height of printable area (imperial)** 1.50 "

**Height of printable area (metric)** 38.1 mm

**Bundle Diameter Min. (Imperial)** 0.39 "

**Bundle Diameter Min. (Metric)** 10.0 mm

**Bundle Diameter Max. (Imperial)** 0.87 "

**Bundle Diameter Max. (Metric)** 22.2 mm

**Horizontal Repeat HR (metric)** 50.8 mm

**Horizontal Repeat HR (imperial)** 2.0 "

**Print Method** Thermal Transfer

**Thickness T (Metric)** 25 µm

**Vertical Repeat VR (imperial)** 4.0 "

**Vertical Repeat VR (metric)** 101.6 mm

**Width of Liner WL (metric)** 55.88 mm

**Width of Liner WL (imperial)** 2.20 "

## Logistics and Packaging

---

**Quantity Per** reel

**Package Quantity** 1000

**Package Quantity (Metric)** 1000

**Carton Quantity** 1000

**Labels per Column** 1

**Labels per Row** 1

**Weight (Metric)** 0.1 kg

## Material and Specifications

---

**Material** Type 100B, Vinyl (PVC), white transparent (WH/CL), self laminating

**Material Shortcut** 100B

**Adhesive** Acrylic

**Adhesive Shortcut** Acrylic

**Adhesive Operating Temperature** -40°F to +194°F (-40°C to +90°C)

**Operating Temperature** -40°F to +194°F (-40°C to +90°C)

**ROHS Compliant** Yes

**Certification/Specification** UL-Recognized