

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TAG75T1-795](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TAG75T1-795

Article Number: 596-75795

Thermal Transfer Label, 2.0" X .625", 1 Across, Polyester, Silver, 2000/RL



Download drawing



Download spec sheet

Base Data

Local Order Number TAG75T1-795

Type TAG75T1

Color Silver (SR)

- Features and Benefits**
- Thermal transfer labels are made with high performance materials for long term industrial applications.
 - Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.
 - The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.

Product Description Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.

Short Description Thermal Transfer Label, 2.0" X .625", 1 Across, Polyester, Silver, 2000/RL

Product Dimensions

Width W (Imperial) 2.0 "

Width W (Metric) 50.8 mm

Height H (Imperial) 0.625 "

Height H (Metric) 15.87 mm

Horizontal Repeat HR (imperial) 2.0 "

Horizontal Repeat HR (metric) 50.8 mm

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 0.75 "

Vertical Repeat VR (metric) 19.05 mm

Width of Liner WL (imperial) 2.12 "

Width of Liner WL (metric) 53.8 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 2000

Package Quantity (Metric) 2000

Labels per Row 1

Material and Specifications

Material Type 795, Polyester, silver matt (SR)



Adhesive Acrylic

Adhesive Operating Temperature -40°F to +300°F (-40°C to +149°C)

Operating Temperature -40°F to +300°F (-40°C to +149°C)

ROHS Compliant Yes

Certification/Specification UL-Recognized

UL Recognized (US and Canada) Yes