

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TAS100LWS](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TAS100LWS



Article Number: 111-98502

Aerial Support Tie, 16.6" Long, 100lb Tensile Strength, 0.88" Spacer, PA66HIRHSUV;PP, Black, 500/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number TAS100LWS

Type TAS100LWS

Color Black (BK)

- Features and Benefits**
- UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.
 - One piece design reduces installation time.
 - Outside serrations prevent cable damage.
 - Bent tail allows for quick installation by hand.

Product Description The Aerial Support Ties feature a one piece design combining the tie and spacer in one part, reducing installation time and inventory costs. The outside serrations along the strap prevent damage to the cables. Manufactured in materials resistant to outdoor environments eliminates the need for maintenance. Bent tail design allows quick and simple installation by hand.

Short Description Aerial Support Tie, 16.6" Long, 100lb Tensile Strength, 0.88" Spacer, PA66HIRHSUV;PP, Black, 500/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 100.0 lbs

Minimum Tensile Strength (Metric) 445.0 N

Length L (Imperial) 16.6 "

Length L (Metric) 421.6 mm

Fixation Method Connector Clip

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Height H (Imperial) 0.88 "

Height H (Metric) 22.4 mm

Bundle Diameter Max. (Imperial) 4.5 "

Bundle Diameter Max. (Metric) 114.3 mm

Logistics and Packaging

Quantity Per box

Package Quantity (Metric) 500

Carton Quantity 500

Material	Polypropylene (PP) Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PP PA66HIRHSUV
Material Cable Tie	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Flammability	UL94 HB
Material Spacer	Polypropylene (PP)
Operating Temperature	-40°F to +230°F (-40°C to +110°C)