

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TELS-SPOOL](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TELS-SPOOL



Article Number: 111-32106

Extended Length Tie, POM, Black, 1-50ft reel of strap/pkg



Download spec sheet

Base Data

Local Order Number TELS-SPOOL

Type TELS-SPOOL

Color Black (BK)

- Features and Benefits**
- Continuous strap and separate heads allow for any bundle diameter, eliminating waste.
 - Smooth strap prevents cable damage.
 - UV resistant materials contain an inhibitor which prolongs the life of the tie in outdoor environments.

Product Description HellermannTyton's Extended Length Tie is a high tensile strength strapping system consisting of a continuous strap and separate locking head making it suitable for any bundle diameter, eliminating waste. The smooth strap and specially designed heads with stainless steel pawls, provides a strong hold on cables and wires without damage during vibration or in extreme environments. Spacers are available for dual bundle applications.

Short Description Extended Length Tie, POM, Black, 1-50ft reel of strap/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 250.0 lbs

Minimum Tensile Strength (Metric) 1112.0 N

Length L (Imperial) 50.0 ft

Length L (Metric) 15.2 m

Fixation Method None

Releasable Closure No

Tie Closure steel pawl

Variant Extended Length

Width W (Imperial) 0.5 "

Width W (Metric) 12.8 mm

Thickness T (Imperial) 0.06 "

Thickness T (Metric) 1.52 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 50 ft

Package Quantity (Metric) 1

Carton Quantity 25

Material and Specifications

Material Polyacetal (POM)

Material Cable Tie	Polyacetal (POM)
Flammability	UL94 HB
Material Head	Polyacetal (POM)
Material Spacer	Polypropylene, UV-resistant (PPW)
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes