

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[TT100OUTSM](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

TT100OUTSM



Article Number: 556-00169

Thermal Transfer Ribbon, 4.33" X 242', .50" Core, 100 Resin, Black, 1/EA



Download spec sheet

Base Data

Local Order Number TT100OUTSM

Type TT100OUTSM

Color Black (BK)

- Features and Benefits**
- Ribbons are resin based for the best print durability.
 - Ribbons are available to fit all HellermannTyton printers for easy resupply.
 - Ribbons are available in colors for maximizing design printing capabilities.
 - Ribbons meet UL recognition and Military standard where applicable to meet specific industry label requirements.

Product Description HellermannTyton thermal transfer ribbons are designed for use in HellermannTyton thermal transfer printers. Available on 1/2" and 1" cores, the ribbons are coated side out and available in two different lengths. All ribbons are available in a variety of colors and are matched to the HellermannTyton label stock to give the best chemical and abrasion resistance.

Short Description Thermal Transfer Ribbon, 4.33" X 242', .50" Core, 100 Resin, Black, 1/EA

Product Dimensions

Length L (Imperial) 242.0 ft

Length L (Metric) 74.0 m

Reel Length (imperial) 242.0 ft

Variant Coloured ribbon

Width W (Imperial) 4.33 "

Width W (Metric) 110.0 mm

Print Method Thermal Transfer

Logistics and Packaging

Quantity Per pieces

Package Quantity 1

Package Quantity (Metric) 1

Carton Quantity 1

Weight (Metric) 0.15 kg

Weight (imperial) 0.662 lbs

Material and Specifications

Material Polyester Film

Material Shortcut PET

Operating Temperature +40°F to +300°F (+4°C to +82°C)



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of TT100OUTSM - BLACK RIBBON, 4.33" X 242'

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Certification/Specification UL-Recognized