

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Molex Connector Corporation](#)
[0260010802](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

CABLE SPECIFICATIONS:

1.- STANDARD KINKED JUMPER SERIES #26001 (24545 CABLE, .128" S/R BOTH ENDS)

2.- PHYSICAL

CONDUCTOR SPACING100" (2.54mm) ϕ TO ϕ
 WIRE GAUGE 24 AWG (1/24), SOLID TINNED
 INSULATION PVC (MOLEX GRAY)
 EDGE MARK COLOR RED

3.- AGENCY

U.L. STYLE 2651
 TEMPERATURE RATING -20 °C TO 105 °C
 VOLTAGE RATING 300V. MAX.
 FLAMMABILITY RATING VW-1

4.- SPECIAL REQUIREMENT

RoHS AND LEAD FREE COMPLIANT
 NO TEXT MARKING ON FCB


5.- GENERAL

NON-OPERATING TEMPERATURE.....-20°C TO 105°C

6.- SOLDERING CONDITION

SOLDER TEMPERATURE.....260°C. MAX.
 SOLDERING TIME.....3 SECOND. MAX.
 INSULATION SHRINK......2MM. NOM


PCB HOLE LAYOUT
 RECOMMENDED HOLE DIA. .042 In.



NOTES:

- 1.- ADD 0.020" TO QTY. OF CABLE.
- 2.- STRIP OF CABLE MUST BE 0.138" TO REMAIN 0.128" AFTER KINK ON EACH END.

STRIP & KINK



OVERALL LENGTH ("A")
 TOLERANCE FOR OAL +/- .100"
 INSULATION LENGTH ("B" REF.)
 DIMS "A" & "B" REFERS TO
 SHOWN IN MATRIX.

MATRIX FOR STANDARD KINKED JUMPER SERIES # 26001 (24545 CABLE)									
LENGTH "A" (±.100")	1.256"	2.256"	3.256"	4.256"	5.256"	6.256"	7.256"	8.256"	
LENGTH "B" (REF.) CIRCUITS	1.000"	2.000"	3.000"	4.000"	5.000"	6.000"	7.000"	8.000"	
3	26001-0301	26001-0302	26001-0303	26001-0304	26001-0305	26001-0306	26001-0307	26001-0308	
4	26001-0401	26001-0402	26001-0403	26001-0404	26001-0405	26001-0406	26001-0407	26001-0408	
5	26001-0501	26001-0502	26001-0503	26001-0504	26001-0505	26001-0506	26001-0507	26001-0508	
6	26001-0601	26001-0602	26001-0603	26001-0604	26001-0605	26001-0606	26001-0607	26001-0608	
7	26001-0701	26001-0702	26001-0703	26001-0704	26001-0705	26001-0706	26001-0707	26001-0708	
8	26001-0801	26001-0802	26001-0803	26001-0804	26001-0805	26001-0806	26001-0807	26001-0808	
9	26001-0901	26001-0902	26001-0903	26001-0904	26001-0905	26001-0906	26001-0907	26001-0908	
10	26001-1001	26001-1002	26001-1003	26001-1004	26001-1005	26001-1006	26001-1007	26001-1008	

26001-***
 A B C

A = STD. KINKED JUMPER I.D. No

B = CIRCUIT SIZE
 3 THRU 10

C = DENOTES LENGTH
 1.000" TO 8.000"

B E-07-0793 B ₁ : ADD GENERAL & SOLDERING CONDITION DATA 07/12/07 A THL2006-0004 NEW RELEASE 06/06/01 REV. HISTORY EC NO. DETAIL DATE	SEE CHANGE DETAIL EC NO: THL2008-0019 2007/12/07 DRW: NCANSAKHOM 2007/12/11 CHK: DANCHALENY 2007/12/11 APPR: SV IRAT JAPOL 2007/12/20	QUALITY SYMBOLS ▽=3 ▽=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE IN/MM		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION				
			4 PLACES ± --- INCH	3 PLACES ± --- INCH	2 PLACES ± --- INCH	1 PLACE ± --- INCH	ANGULAR ± --- °	DRAWN BY CPANSAKHOM DATE 2006/06/01 CHECKED BY PMEECHAI DATE 2006/06/01 APPROVED BY SV IRAT JAPOL DATE 2006/06/01	TITLE STANDARD KINKED TAIL JMP .100" CTR PVC INSULATED 24 AWG SOLID TINNED	MOLEX INCORPORATED	MATERIAL NO. SEE CHART	DOCUMENT NO. SD-26001-001	SHEET NO. 1 OF 1
			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS					THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					

tb_frame_A4_P_ME_T
 Rev. E 2006/04/15

6

5

4

3

2

1