

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[151-10905](#)

For any questions, you can email us directly:
sales@integrated-circuit.com

HellermannTyton

151-10905

Article Number: 151-10905

Q Mount with Adhesive, 1.2" x 1.2" x 0.21", 4 way entry for Q18 thru Q50 ties, PA66, White, 100/bag



Download drawing



Download spec sheet

Base Data

Local Order Number 151-10905

Type QM30A

Color Natural (NA)

Features and Benefits • 2- or 4-way entry options for the Q Tie, offering flexibility and stability

Product Description Q Mounts are designed to work exclusively with the Q Tie cable tie series. This mounting component is available with adhesive or can be secured with screws. The Q Mount allows either a 2- or 4-way entry for the Q Tie, providing a quick and simple insertion into the mount. Once in place, the Q Tie will not slip out, even in vertical mounting applications.

Short Description Q Mount with Adhesive, 1.2" x 1.2" x 0.21", 4 way entry for Q18 thru Q50 ties, PA66, White, 100/bag

Product Dimensions

Length L (Imperial) 1.2 "

Length L (Metric) 30.0 mm

Fixation Method Screw Mounting and Adhesive

Width W (Imperial) 1.2 "

Width W (Metric) 30.0 mm

Cable Tie Width Max. (Imperial) 0.2 "

Cable Tie Width Max. (Metric) 5.1 mm

Height H (Imperial) 0.21 "

Height H (Metric) 4.5 mm

Mounting Hole Diameter D (Imperial) 0.16 "

Mounting Hole Diameter D (Metric) 4.1 mm

Mounting Hole Diameter D Min. (Imperial) 0.16 "

Mounting Hole Centers (Imperial) 0.83 "

Mounting Hole Diameter D Max. (Metric) 4.1 mm

Mounting Hole Diameter D Min. (Metric) 4.1 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Material and Specifications

Material Polyamide 6.6 (PA66)

Adhesive Shortcut Synthetic rubber T60

Adhesive Synthetic rubber with base of polyethylene foam

Adhesive Operating Temperature -40°F to +140°F (-40°C to +60°C)

Flammability UL94 V2 (excluding adhesive)

Halogenfree Yes

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes