

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03164](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

170-03164



Article Number: 170-03164

Nomex(R) High Temperature Woven Sleeveing, 1.25" Dia., Green, 100.0 ft/Bulk Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03164

Type BSNMX1145B

Color Green (GN)

Features and Benefits

- Self extinguishing material does not melt and is unaffected by most acids, and provides excellent thermal stability against direct flame.
- Meets FMVSS 302 specifications for use in automotive engineering.
- Material cuts with ordinary scissors which reduces assembly time.

Product Description A densely woven aramid fiber sleeveing, this soft and flexible material is self extinguishing and can withstand temperatures reaching up to 662°F.

Short Description Nomex(R) High Temperature Woven Sleeveing, 1.25" Dia., Green, 100.0 ft/Bulk Reel

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Bundle Diameter Min. (Imperial) 1.0 "

Bundle Diameter Min. (Metric) 25.4 mm

Bundle Diameter Max. (Imperial) 1.5 "

Bundle Diameter Max. (Metric) 38.1 mm

Nominal Diameter (Imperial) 1-1/4 "

Nominal Diameter (Metric) 31.8 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 100 ft

Weight (Metric) 1.58 kg

Weight (imperial) 3.5 lbs

Material and Specifications

Material Polyaramid Polymetaphenylene Isophthalamide

Material Shortcut NOMEX®

ROHS Compliant Yes

