

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[170-03187](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

170-03187



Article Number: 170-03187

Flame Retardant Expandable Braided Sleeving, 3/8" Dia., Black, 500ft/Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03187

Type BSPFR380

Color Black (BK)

Features and Benefits

- Treated polyester material contains a combustion inhibitor for use in applications where flame retardancy is required.
- Braided design allows sleeving to expand by 150% to accommodate variations in wire bundle and eases installation.

Product Description A flame retardant woven (threaded) polyester sleeving that is resistant to cuts and abrasion, and contains a combustion inhibitor allowing it to achieve a UL and CSA flame resistance rating of VW-1. Contains white tracer thread for easy identification.

Short Description Flame Retardant Expandable Braided Sleeving, 3/8" Dia., Black, 500ft/Reel

Product Dimensions

Length L (Imperial) 500.0 ft

Length L (Metric) 152.4 m

Reel Length (imperial) 500.0 ft

Bundle Diameter Min. (Imperial) 0.188 "

Bundle Diameter Min. (Metric) 4.8 mm

Bundle Diameter Max. (Imperial) 0.5 "

Bundle Diameter Max. (Metric) 12.7 mm

Diameter D (imperial) 0.375 "

Diameter D (metric) 9.53 mm

Nominal Diameter (Imperial) 3/8 "

Nominal Diameter (Metric) 9.5 mm

Logistics and Packaging

Quantity Per box

Package Quantity 500.0 ft

Package Quantity (Metric) 500 ft

Carton Quantity 500.0 ft

Material and Specifications

Material Polyester (PET)

Material Shortcut PET



Flammability VW-1
FAR 25
FMVSS 302
Mil-202

Operating Temperature -94°F to +257°F (-70°C to +125°C)

ROHS Compliant Yes

UL Recognized (US and Canada) Yes