Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

HellermannTyton 181-00174

For any questions, you can email us directly: sales@integrated-circuit.com



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 181-00174 - SD1X3 GRAY PVC DUCT MOD

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

HellermannTyton

181-00174

Article Number: 181-00174

Solid Wall Wiring Duct, 1" X 3", Non-Adhesive, PVC, Gray, 30ft/Box







Base Data

Local Order Number 181-00174

Type SD1X3

Color Gray (GY)

Features and Benefits • A temporary film is applied to the covers to protect against scratches and is writable for identification during

installation.

· Cover is flush with the side of the duct for increased wire capacity and allows for tight, side by side duct placement.

· Covers are provided with a non-slip lining, which insures the covers remain in place during vibration, yet they easily

snap on and off. (Covers to be purchased separately)

Product Description HellermannTyton's Pro-Duct solid wall wiring duct efficiently routes and protects wires and cables. Solid wall wiring

duct is designed for straight wire runs where breakouts are not required. Pro-Duct solid wall wiring duct is manufactured from high-impact, rigid PVC, and is available in 6-foot lengths in standard colors of white, gray and

Short Description Solid Wall Wiring Duct, 1" X3", Non-Adhesive, PVC, Gray, 30ft/Box

Product Dimensions

Length L (Imperial) 6.0 ft

Length L (Metric) 1.83 m

Width W (Imperial) 1.0 "

Width W (Metric) 25.4 mm

Width W2 (Imperial) 1.0 "

Width W2 (Metric) 25.4 mm

Height H (Imperial) 3.07 "

Height H (Metric) 77.9 mm

Mounting Hole Centers (Imperial) 4.0 "

Logistics and Packaging

Quantity Per box

Package Quantity 30.0 ft

Package Quantity (Metric) 9.1 m

Carton Quantity 120.0 ft

Material and Specifications

Material Polyvinylchloride (PVC)

Material Shortcut PVC



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 181-00174 - SD1X3 GRAY PVC DUCT MOD

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Operating Temperature +122°F (+50°C)

ROHS Compliant Yes

Certification/Specification CSA

UL

UL Listed (US and Canada) No

UL Recognized (US) Yes

UL Recognized (US and Canada) No

© HellermannTyton 2015