

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[181-00608](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

181-00608



**Article Number: 181-00608**

**High Density Slotted Wall Wiring Duct, 2" X 2", Non-Adhesive, PVC, Black, 120ft/Carton**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 181-00608

**Type** SLHD2X2

**Color** Black (BK)

**Features and Benefits**

- Narrow fingers reduce fanning of the wires to the terminal blocks, presenting a neater appearance.
- Each finger is provided with a double restriction to hold wires in the bottom portion of the duct, allowing for easier installation.
- Mounting holes are uniform in size to the solid and slotted wall duct, but are offered every 2 inches to accommodate compact designs and ease installation.

**Product Description** Pro-Duct high density, slotted wiring duct features narrow fingers, a 2 to 1 finger ratio compared to standard slotted wiring duct. With the narrow fingers, compact designs and components are more easily accommodated.

**Short Description** High Density Slotted Wall Wiring Duct, 2" X 2", Non-Adhesive, PVC, Black, 120ft/Carton

## Product Dimensions

**Length L (Imperial)** 6.0 ft

**Length L (Metric)** 1.83 m

**Width W (Imperial)** 2.0 "

**Width W (Metric)** 50.8 mm

**Width W2 (Imperial)** 2.0 "

**Width W2 (Metric)** 50.8 mm

**Width W3 (Imperial)** 0.16 "

**Width W3 (Metric)** 4.1 mm

**Width W4 (imperial)** 0.4 "

**Width W4 (metric)** 10.2 mm

**Width W5 (imperial)** 1.6 "

**Width W5 (metric)** 40.6 mm

**Width W6 (imperial)** 0.5 "

**Width W6 (metric)** 12.7 mm

**Height H (Imperial)** 2.07 "

**Height H (Metric)** 52.6 mm

**Mounting Hole Centers (Imperial)** 2.0 "

## Logistics and Packaging

**Quantity Per** carton

**Package Quantity** 120.0 ft



**Package Quantity (Metric)** 36.6 m

**Carton Quantity** 120.0 ft

## Material and Specifications

---

**Material** Polyvinylchloride (PVC)

**Material Shortcut** PVC

**Flammability** self-extinguishing

**Operating Temperature** +122°F (+50°C)

**ROHS Compliant** Yes

**Certification/Specification** CSA  
UL

**UL Listed (US and Canada)** No

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** No