

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)
[558-00382](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

558-00382

Article Number: 558-00382

Banded Continuous Colored Signal Panel Roll, 4.0" X 250', UV Stable, Orange/White, 250ft/RL



Download spec sheet

Base Data

Local Order Number 558-00382

Type HT4OE10250UV

Color Orange (OG)

Features and Benefits

- Continuous Colored Signal Panel labels come with yellow or orange stripes for easy printing of caution and warning labels.
- Continuous labels allow for designing and cutting labels to any length.
- Various widths are available so that a wide variety of sign sizes can be customized and produced on demand.

Product Description The Pre-printed colored header vinyl rolls can be used to design signs that conform to Occupational Safety and Hazard Association (OSHA) and American National Standards Institute (ANSI) requirements for Warning and Caution Signs and markers. All can be designed, printed and cut to length in Tagprint Pro and any HellermannTyton thermal transfer printing system.

Short Description Banded Continuous Colored Signal Panel Roll, 4.0" X 250', UV Stable, Orange/White, 250ft/RL

Product Dimensions

Length L (Imperial) 250.0 ft

Length L (Metric) 76.2 m

Width W (Imperial) 4.0 "

Width W (Metric) 101.6 mm

Height H (Imperial) 4.0 "

Height H (Metric) 101.6 mm

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 4.0 "

Vertical Repeat VR (metric) 101.6 mm

Width of Liner WL (metric) 101.6 mm

Width of Liner WL (imperial) 4.0 "

Logistics and Packaging

Quantity Per reel

Package Quantity 250

Package Quantity (Metric) 250

Labels per Column 1

Labels per Row 1

Material and Specifications

Material Shortcut 840/926

Adhesive Acrylic

Adhesive Shortcut Acrylic

Adhesive Operating Temperature -40°F to +180°F (-40°C to +82°C)

Halogenfree Yes

Operating Temperature -40°F to +302°F (-40°C to +150°C)

ROHS Compliant Yes

Certification/Specification UL969