

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[596-00372](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00372

Article Number: 596-00372

Pre-Printed Header Label, SAFETY, 3" X 2", PET, Green, 250/RL



Download spec sheet

## Base Data

Local Order Number 596-00372

Type 3X2SAFETY

Color Green (GN)

- Features and Benefits**
- Made with UV stable inks and materials for durability and weather resistance
  - Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.
  - High abrasion and scuff resistance for high performance labeling.
  - Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections

**Product Description** HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

**Short Description** Pre-Printed Header Label, SAFETY, 3" X 2", PET, Green, 250/RL

## Product Dimensions

Width W (Imperial) 3.0 "

Width W (Metric) 76.2 mm

Height H (Imperial) 2.0 "

Height H (Metric) 50.8 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 250

Package Quantity (Metric) 250

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Adhesive Shortcut Acrylic

Adhesive Acrylic

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Halogenfree Yes

Operating Temperature -40°F to +302°F (-40°C to +150°C)

ROHS Compliant Yes



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 596-00372 - SAFETY, 3 X 2, 250/RL

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**UL Recognized (US)** Yes

---

© HellermannTyton 2015