

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)  
[596-00379](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00379

Article Number: 596-00379

Pre-Printed Header Label, DANGER, Blank Yellow Triangle, 1.35" X 2.75", PET, Red, 250/RL



Download spec sheet

## Base Data

Local Order Number 596-00379

Type DV275X135

Color Red (RD)

**Features and Benefits**

- Pre-Printed Signal Word labels come with the header pre-printed in colors so that only one color of ribbon is needed to complete the message panel.
- Labels are pre-made to the most recent ANSI standards so that code compliance is assured.
- Pre-Printed Signal Panel labels can be printed using standard thermal transfer printers to reduce labor, eliminate minimum orders and allow the user to create labels on demand when needed.

**Product Description** Pre-Printed Signal word labels come pre-printed with the NOTICE, CAUTION, DANGER and SAFETY headers in blue, yellow, red and green as defined by ANSI Z535. The variable body text and be printed using Tagprint Pro labeling software and the HellermannTyton line of thermal transfer printers or any standard thermal transfer printer. Only one color needs to be printed to complete the label, saving time and money.

**Short Description** Pre-Printed Header Label, DANGER, Blank Yellow Triangle, 1.35" X 2.75", PET, Red, 250/RL

## Product Dimensions

Length L (Imperial) 2.75 "

Length L (Metric) 69.85 mm

Width W (Imperial) 1.35 "

Width W (Metric) 34.29 mm

Height H (Imperial) 2.75 "

Height H (Metric) 69.85 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 250

Package Quantity (Metric) 250

Labels per Column 1

Labels per Row 1

Weight (imperial) 1.68 oz

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Adhesive Acrylic

Adhesive Shortcut Acrylic



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 596-00379 - DANGER 1.35 X 2.75 250/RL

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Adhesive Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**Operating Temperature** -40°F to +302°F (-40°C to +150°C)

**ROHS Compliant** Yes