



Distributor of HellermannTyton: Excellent Integrated System Limited

Datasheet of 596-00381 - .50" X 100' 1/RL

Contact us: sales@integrated-circuit.com Website: www.integrated-circuit.com

Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[596-00381](#)

For any questions, you can email us directly:

sales@integrated-circuit.com

HellermannTyton

596-00381

Article Number: 596-00381

Terminal Block label, .50" wide, PE, White, 100ft/RL



Download spec sheet

Base Data

Local Order Number 596-00381

Type TBL500

Color White (WH)

- Features and Benefits**
- Label stock for use with thermal transfer printers.
 - Strong acrylic adhesive for industrial applications.
 - Abrasion and chemical resistant top coat for long lasting results.
 - For use with HellermannTyton thermal transfer printers or most standard brands.

Product Description To suit different industrial applications, HellermannTyton offers a wide variety of thermal transfer label stocks including polyester, metalized polyester, clear polyester, cloth, polyimide and Durattach high density polyolefin. Thermal transfer labels include a strong acrylic adhesive and abrasion and chemical resistant top coatings for long lasting results. Easily print custom labels and variable information with HellermannTyton TagPrint® Pro labeling software and a thermal transfer printer.

Short Description Terminal Block label, .50" wide, PE, White, 100ft/RL

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Height H (Imperial) 0.5 "

Height H (Metric) 12.7 mm

Print Method Thermal Transfer

Logistics and Packaging

Quantity Per reel

Package Quantity 100 ft

Package Quantity (Metric) 30.48 m

Labels per Column 1

Labels per Row 1

Material and Specifications

Material Polyethylene (PE)

Material Shortcut PE

Adhesive Rubber



Adhesive Operating Temperature -40°F to +176°F (-40°C to +80°C)

Halogenfree Yes

Operating Temperature -40°F to +176°F (-40°C to +80°C)

ROHS Compliant Yes

UL Recognized (US) No