



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 596-00624 - .275" X 100' 1/RL

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

## **Excellent Integrated System Limited**

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[HellermannTyton](#)

[596-00624](#)

For any questions, you can email us directly:

[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

# HellermannTyton

596-00624

Article Number: 596-00624

Terminal Block Label, .275" wide, PE, White, 100ft/RL



Download spec sheet

## Base Data

Local Order Number 596-00624

Type TBL275

Color White (WH)

- Features and Benefits**
- Label stock for use with thermal transfer printers.
  - Strong acrylic adhesive for industrial applications.
  - Abrasion and chemical resistant top coat for long lasting results.
  - For use with HellermannTyton thermal transfer printers or most standard brands.

**Product Description** To suit different industrial applications, HellermannTyton offers a wide variety of thermal transfer label stocks including polyester, metalized polyester, clear polyester, cloth, polyimide and Durattach high density polyolefin. Thermal transfer labels include a strong acrylic adhesive and abrasion and chemical resistant top coatings for long lasting results. Easily print custom labels and variable information with HellermannTyton TagPrint® Pro labeling software and a thermal transfer printer.

**Short Description** Terminal Block Label, .275" wide, PE, White, 100ft/RL

## Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Width W (Imperial) 100.0 ft

Width W (Metric) 3048 mm

Height H (Imperial) 0.275 "

Height H (Metric) 6.98 mm

Print Method Thermal Transfer

## Logistics and Packaging

Quantity Per reel

Package Quantity 100

Package Quantity (Metric) 100

Labels per Column 1

Labels per Row 1

## Material and Specifications

Material Polyethylene (PE)

Material Shortcut PE

Adhesive Operating Temperature -40°F to +300°F (-40°C to +149°C)



**Distributor of HellermannTyton: Excellent Integrated System Limited**

Datasheet of 596-00624 - .275" X 100' 1/RL

Contact us: [sales@integrated-circuit.com](mailto:sales@integrated-circuit.com) Website: [www.integrated-circuit.com](http://www.integrated-circuit.com)

---

**Halogenfree** Yes

**Operating Temperature** -40°F to +300°F (-40°C to +149°C)

**ROHS Compliant** Yes

**UL Recognized (US)** Yes