

## Excellent Integrated System Limited

Stocking Distributor

Click to view price, real time Inventory, Delivery & Lifecycle Information:

[Panduit](#)

[LCAX750-58H-3](#)

For any questions, you can email us directly:


[sales@integrated-circuit.com](mailto:sales@integrated-circuit.com)

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.

|                                                |                                                                                                                                                |
|------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| Material                                       | High Conductivity Seamless Copper Tube                                                                                                         |
| Plating                                        | Electro-Tin                                                                                                                                    |
| Wire Size                                      | 750 STR/FLEX                                                                                                                                   |
| Wire Type                                      | Stranded Copper: Class B & C, Compact, Class G, H, I, K, M, Locomotive                                                                         |
| Wire Strip Length                              | 1-3/4 in.                                                                                                                                      |
| Stud Size                                      | 5/8 in.                                                                                                                                        |
| UL Listed Wire Connector                       | Yes, for applications up to 35kv. Consult cable manufacturer for voltage stress relief instructions with applications greater than 2000 volts. |
| UL Temperature Rating                          | 90 ° C                                                                                                                                         |
| C.S.A Certified Wire Connector                 | Yes                                                                                                                                            |
| Panduit Color Code on Barrel                   | YELLOW                                                                                                                                         |
| Panduit Die Index No. on Barrel                | P115                                                                                                                                           |
| Alternate Industry Die Index No. ( ) on Barrel | (L115)                                                                                                                                         |



LISTED  
Wire Connector



|     |      |      |      |             |       |                                                               |     |
|-----|------|------|------|-------------|-------|---------------------------------------------------------------|-----|
|     |      |      |      |             |       | <b>PANDUIT CORP. TINLEY PARK, ILLINOIS</b>                    |     |
|     |      |      |      |             |       | LCAX750-58H-3                                                 |     |
|     |      |      |      |             |       | Copper Lug - One-Hole, Standard Flex Barrel, 45° Angle Tongue |     |
| 00  | 8/04 | JHNU | TLCO | RELEASED    | 11206 | SCALE                                                         | N/A |
| REV | DATE | BY   | CHK  | DESCRIPTION | ECN   | DRAWING NO / CAD FILE                                         |     |
|     |      |      |      |             |       | LCAX750-58H-CUST                                              |     |